



Package Code 2

<p>Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches</p>	Revisions				Impellimax		
	Rev	Number	Date	By	OUTLINE		
	A	ECO 1852	3/17/99	PC			
B	ECO 2233	1/28/02	PC	Drawn By:	Date:	Sheet 1 of 2	
				P.C.	11/3/93		
<p>Information herein is believed accurate. Suitability not guaranteed.</p>				DRF:	Date:	Approved:	Drawing # 9618-50
					11/3/93	P.C.	

PIN	CONNECTION	PIN	CONNECTION
1	-5V	14	NC
2	Output 1	13	Output 2
3	Ground	12	NC
4	NC	11	NC
5	NC	10	NC
6	Input 1	9	Input 2
7	+5v	8	NC

Notes:

- 1) Inputs are TTL compatible.
- 2) Outputs are independent and noninverting. Output current is +/- 25 mA nominal, +/-20 mA minimum, at +/-5V into a 39 ohm resistor. Outputs provide current spikes.
- 3) Switching speed is 8 nsec typical into a resistive load.
- 4) Unit contains internal .01 bypass caps on supplies.

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<u>Impellimax</u>		
	Rev	Number	Date	By			
	A	ECO 1852	3/17/99	PC	OUTLINE		
	B	ECO 2233	1/28/02	PC			
Information herein is believed accurate. Suitability not guaranteed.					Drawn By:	Date:	Sheet 2 of 2
					P.C.	11/3/93	
					DRF:	Date:	Drawing # 9618-50
					11/3/93	Approved: P.C.	