



Package Code 4

<p>Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches</p>	Revisions				Impellimax			
	Rev	Number	Date	By	OUTLINE			
					<p>Drawn By: P.C.</p>	<p>Date: 8/25/00</p>	<p>Sheet 1 of 2</p>	
<p>Information herein is believed accurate. Suitability not guaranteed.</p>					<p>DRF: 500</p>	<p>Date: 8/25/00</p>	<p>Approved: P.C.</p>	<p>Drawing # 9512-50</p>

PIN	CONNECTION	PIN	CONNECTION
1	+5V	22	GROUND
2	IN A	21	NC
3	IN B	20	NC
4	ENABLE	19	NC
5	NC	18	NC
6	$\overline{\text{OUT 4}}$	17	$\overline{\text{OUT 1}}$
7	OUT 4	16	OUT 1
8	NC	15	NC
9	$\overline{\text{OUT 3}}$	14	$\overline{\text{OUT 2}}$
10	OUT 3	13	OUT 2
11	VEE INT	12	GROUND

Notes:

- 1) Unit accepts two bit binary TTL inputs (pin 2 and pin 3) and select one of four channels. Enable (pin 4) must be high for decoding operation.
- 2) Outputs are not current limited. Use external resistors to limit positive output current to 15 mA max. Negative outputs are for back bias only.
- 3) Switching speed is 60 nsec typical, 80 nsec max.

	INPUT		CH 1		CH 2		CH 3		CH 4		
PIN #	2	3	4	16	17	13	14	10	9	7	6
	0	0	1	*-V	0	0	-V	0	-V	0	-V
	1	0	1	0	-V	*-V	0	0	-V	0	-V
	0	1	1	0	-V	0	-V	*-V	0	0	-V
	1	1	1	0	-V	0	-V	0	-V	*-V	0
	X	X	0	0	-V	0	-V	0	-V	0	-V

* = Selected Channel

Supply Current (no loads) : +5V typical, 35 mA / -V typical , 20 mA

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<p style="text-align: center;">Impellimax</p> <p style="text-align: center;">OUTLINE</p>			
	Rev	Number	Date	By				
Information herein is believed accurate. Suitability not guaranteed.					Drawn By: P.C.	Date: 8/25/00	Sheet 2 of 2	
					DRF: 500	Date: 8/25/00	Approved: P.C.	Drawing # 9512-50