



<p>Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches</p>	Revisions				<u>Impellimax</u>	
	A	ECO 2149	4/6/01	P.C.	OUTLINE	
						Sheet 1 of 2
<p>Information herein is believed accurate. Suitability not guaranteed.</p>					Drawn By: P.C.	Date: 8/9/90
					DRF: NA	Approved: P.C.
						Drawing # NS3-50

PIN	CONNECTION	PIN	CONNECTION
1	+5 V	22	NC
2	Input 1	21	NC
3	Output 1	20	NC
4	Input 2	19	NC
5	Output 2	18	NC
6	Input 3	17	NC
7	Output 3	16	NC
8	NC	15	NC
9	NC	14	NC
10	Vee	13	NC
11	Ground	12	NC

Notes:

- 1) Channels are independent and noninverting.
- 2) Switching speed is 60 nsec typical into resistive loads. Outputs are not spiked.
- 3) Negative output current increases with increasing negative voltage.
- 4) Unit contains internal .01 uF bypass capacitors on both power supplies.

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<u>Impellimax</u>		
	A	ECO 2149	4/6/01	P.C.	OUTLINE		
							Sheet 2 of 2
Information herein is believed accurate. Suitability not guaranteed.					Drawn By: P.C.	Date: 8/9/90	Drawing #
					DRF: NA	Approved: P. C.	NS3-50