



<p>Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches</p>	Revisions				<u>Impellimax</u>		
	A	ECO 1608	9/15/95	PC	OUTLINE		
	B	ECO 2128	2/12/01				
<p>Information herein is believed accurate. Suitability not guaranteed.</p>						Sheet 1 of 2	
				Drawn By:	Date:	Drawing # NS8-50	
				P.C.	1/29/91		
				DRF:	Approved:		
					P. C.		

PIN	CONNECTION	PIN	CONNECTION
1	+ 5 V	22	- V
2	Input 1	21	Output 8
3	Output 1	20	Input 8
4	Input 2	19	Output 7
5	Output 2	18	Input 7
6	Input 3	17	Output 6
7	Output 3	16	Input 6
8	Input 4	15	Output 5
9	Output 4	14	Input 5
10	NC	13	NC
11	Ground	12	Ground

Notes:

- 1) Channels are independent and noninverting.
- 2) Switching speed is 60 nsec typical into resistive loads. Outputs are not spiked.
- 3) Negative output current increases with increasing negative voltage.
- 4) Unit contains internal .01 uF bypass capacitors on both power supplies.
- 5) Quiescent +5V current is 40 mA max. Negative quiescent current is less than 5 mA for each negative out channel.

Tolerances Except as Noted .x = +/- .05 .xx = +/- .01 .xxx = +/- .005 Dimensions in inches	Revisions				<u>Impellimax</u>		
	A	ECO 1608	9/15/95	PC	OUTLINE		
	B	ECO 2128	2/12/01				
Information herein is believed accurate. Suitability not guaranteed.							Sheet 2 of 2
					Drawn By: J.P.	Date: 1/29/91	Drawing # NS8-50
				DRF:	Approved: P.C		